

Artikelnummer	Innenabmessungen						Abmessungen Schwingrahmen			Aussenabmessungen in mm		
	L*	B*	H*	Deckeltiefe vorne	Mittelteil Länge	Deckeltiefe hinten	Einschub höhe a	Einschub breite b	Einschub tiefe c	L	B	H
4U280VSL	490	580	310	80	330	80	179	450	280	530	630	350
5U280VSL	490	580	355	80	330	80	224	450	280	530	630	395
6U280VSL	490	580	399	80	330	80	268	450	280	530	630	440
7U280VSL	490	580	444	80	330	80	313	450	280	530	630	485
8U280VSL	490	580	488	80	330	80	357	450	280	530	630	530
9U280VSL	490	580	533	80	330	80	402	450	280	530	630	575
10U280VSL	490	580	577	80	330	80	446	450	280	530	630	620
11U280VSL	490	580	622	80	330	80	491	450	280	530	630	665
12U280VSL	490	580	666	80	330	80	535	450	280	530	630	710
4U360VSL	570	580	310	80	410	80	179	450	360	610	630	350
5U360VSL	570	580	355	80	410	80	224	450	360	610	630	395
6U360VSL	570	580	399	80	410	80	268	450	360	610	630	440
7U360VSL	570	580	444	80	410	80	313	450	360	610	630	485
8U360VSL	570	580	488	80	410	80	357	450	360	610	630	530
9U360VSL	570	580	533	80	410	80	402	450	360	610	630	575
10U360VSL	570	580	577	80	410	80	446	450	360	610	630	620
11U360VSL	570	580	622	80	410	80	491	450	360	610	630	665
12U360VSL	570	580	666	80	410	80	535	450	360	610	630	710
4U440VSL	650	580	310	80	490	80	179	450	440	690	630	350
5U440VSL	650	580	355	80	490	80	224	450	440	690	630	395
6U440VSL	650	580	399	80	490	80	268	450	440	690	630	440
7U440VSL	650	580	444	80	490	80	313	450	440	690	630	485
8U440VSL	650	580	488	80	490	80	357	450	440	690	630	530
9U440VSL	650	580	533	80	490	80	402	450	440	690	630	575
10U440VSL	650	580	577	80	490	80	446	450	440	690	630	620
11U440VSL	650	580	622	80	490	80	491	450	440	690	630	665
12U440VSL	650	580	666	80	490	80	535	450	440	690	630	710
4U440VSLT	660	580	310	80	490	90	179	450	440	720	630	370
5U440VSLT	660	580	355	80	490	90	224	450	440	720	630	415
6U440VSLT	660	580	399	80	490	90	268	450	440	720	630	460
7U440VSLT	660	580	444	80	490	90	313	450	440	720	630	505

Artikelnummer	Innenabmessungen						Abmessungen Schwingrahmen			Aussenabmessungen in mm		
	L*	B*	H*	Decktiefe vorne	Mittelteil Länge	Decktiefe hinten	Einschub höhe a	Einschub breite b	Einschub tiefe c	L	B	H
8U440VSLT	660	580	488	80	490	90	357	450	440	720	630	550
9U440VSLT	660	580	533	80	490	90	402	450	440	720	630	595
10U440VSLT	660	580	577	80	490	90	446	450	440	720	630	640
11U440VSLT	660	580	622	80	490	90	491	450	440	720	630	685
12U440VSLT	660	580	666	80	490	90	535	450	440	720	630	730
4U520VSL	730	580	310	80	570	80	179	450	520	770	630	350
5U520VSL	730	580	355	80	570	80	224	450	520	770	630	395
6U520VSL	730	580	399	80	570	80	268	450	520	770	630	440
7U520VSL	730	580	444	80	570	80	313	450	520	770	630	485
8U520VSL	730	580	488	80	570	80	357	450	520	770	630	530
9U520VSL	730	580	533	80	570	80	402	450	520	770	630	575
10U520VSL	730	580	577	80	570	80	446	450	520	770	630	620
11U520VSL	730	580	622	80	570	80	491	450	520	770	630	665
12U520VSL	730	580	666	80	570	80	535	450	520	770	630	710
4U520VSLT	740	580	310	80	570	90	179	450	520	800	630	370
5U520VSLT	740	580	355	80	570	90	224	450	520	800	630	415
6U520VSLT	740	580	399	80	570	90	268	450	520	800	630	460
7U520VSLT	740	580	444	80	570	90	313	450	520	800	630	505
8U520VSLT	740	580	488	80	570	90	357	450	520	800	630	550
9U520VSLT	740	580	533	80	570	90	402	450	520	800	630	595
10U520VSLT	740	580	577	80	570	90	446	450	520	800	630	640
11U520VSLT	740	580	622	80	570	90	491	450	520	800	630	685
12U520VSLT	740	580	666	80	570	90	535	450	520	800	630	730
4U600VSL	810	580	310	80	650	80	179	450	600	850	630	350
5U600VSL	810	580	355	80	650	80	224	450	600	850	630	395
6U600VSL	810	580	399	80	650	80	268	450	600	850	630	440
7U600VSL	810	580	444	80	650	80	313	450	600	850	630	485
8U600VSL	810	580	488	80	650	80	357	450	600	850	630	530
9U600VSL	810	580	533	80	650	80	402	450	600	850	630	575
10U600VSL	810	580	577	80	650	80	446	450	600	850	630	620
11U600VSL	810	580	622	80	650	80	491	450	600	850	630	665

Artikelnummer	Innenabmessungen						Abmessungen Schwingrahmen			Aussenabmessungen in mm		
	L*	B*	H*	Decktiefe vorne	Mittelteil Länge	Decktiefe hinten	Einschub höhe a	Einschub breite b	Einschub tiefe c	L	B	H
12U600VSL	810	580	666	80	650	80	535	450	600	850	630	710
4U600VSLT	820	580	310	80	650	90	179	450	600	880	630	370
5U600VSLT	820	580	355	80	650	90	224	450	600	880	630	415
6U600VSLT	820	580	399	80	650	90	268	450	600	880	630	460
7U600VSLT	820	580	444	80	650	90	313	450	600	880	630	505
8U600VSLT	820	580	488	80	650	90	357	450	600	880	630	550
9U600VSLT	820	580	533	80	650	90	402	450	600	880	630	595
10U600VSLT	820	580	577	80	650	90	446	450	600	880	630	640
11U600VSLT	820	580	622	80	650	90	491	450	600	880	630	685
12U600VSLT	820	580	666	80	650	90	535	450	600	880	630	730
4U680VSL	890	580	310	80	730	80	179	450	680	930	630	350
5U680VSL	890	580	355	80	730	80	224	450	680	930	630	395
6U680VSL	890	580	399	80	730	80	268	450	680	930	630	440
7U680VSL	890	580	444	80	730	80	313	450	680	930	630	485
8U680VSL	890	580	488	80	730	80	357	450	680	930	630	530
9U680VSL	890	580	533	80	730	80	402	450	680	930	630	575
10U680VSL	890	580	577	80	730	80	446	450	680	930	630	620
11U680VSL	890	580	622	80	730	80	491	450	680	930	630	665
12U680VSL	890	580	666	80	730	80	535	450	680	930	630	710
4U680VSLT	900	580	310	80	730	90	179	450	680	960	630	370
5U680VSLT	900	580	355	80	730	90	224	450	680	960	630	415
6U680VSLT	900	580	399	80	730	90	268	450	680	960	630	460
7U680VSLT	900	580	444	80	730	90	313	450	680	960	630	505
8U680VSLT	900	580	488	80	730	90	357	450	680	960	630	550
9U680VSLT	900	580	533	80	730	90	402	450	680	960	630	595
10U680VSLT	900	580	577	80	730	90	446	450	680	960	630	640
11U680VSLT	900	580	622	80	730	90	491	450	680	960	630	685
12U680VSLT	900	580	666	80	730	90	535	450	680	960	630	730
4U760VSL	970	580	310	80	810	80	179	450	760	1010	630	350
5U760VSL	970	580	355	80	810	80	224	450	760	1010	630	395
6U760VSL	970	580	399	80	810	80	268	450	760	1010	630	440

Artikelnummer	Innenabmessungen						Abmessungen Schwingrahmen			Aussenabmessungen in mm		
	L*	B*	H*	Decktiefe vorne	Mittelteil Länge	Decktiefe hinten	Einschub höhe a	Einschub breite b	Einschub tiefe c	L	B	H
7U760VSL	970	580	444	80	810	80	313	450	760	1010	630	485
8U760VSL	970	580	488	80	810	80	357	450	760	1010	630	530
9U760VSL	970	580	533	80	810	80	402	450	760	1010	630	575
10U760VSL	970	580	577	80	810	80	446	450	760	1010	630	620
11U760VSL	970	580	622	80	810	80	491	450	760	1010	630	665
12U760VSL	970	580	666	80	810	80	535	450	760	1010	630	710
4U760VSLT	980	580	310	80	810	90	179	450	760	1040	630	370
5U760VSLT	980	580	355	80	810	90	224	450	760	1040	630	415
6U760VSLT	980	580	399	80	810	90	268	450	760	1040	630	460
7U760VSLT	980	580	444	80	810	90	313	450	760	1040	630	505
8U760VSLT	980	580	488	80	810	90	357	450	760	1040	630	550
9U760VSLT	980	580	533	80	810	90	402	450	760	1040	630	595
10U760VSLT	980	580	577	80	810	90	446	450	760	1040	630	640
11U760VSLT	980	580	622	80	810	90	491	450	760	1040	630	685
12U760VSLT	980	580	666	80	810	90	535	450	760	1040	630	730
4U840VSL	1050	580	310	80	890	80	179	450	840	1090	630	350
5U840VSL	1050	580	355	80	890	80	224	450	840	1090	630	395
6U840VSL	1050	580	399	80	890	80	268	450	840	1090	630	440
7U840VSL	1050	580	444	80	890	80	313	450	840	1090	630	485
8U840VSL	1050	580	488	80	890	80	357	450	840	1090	630	530
9U840VSL	1050	580	533	80	890	80	402	450	840	1090	630	575
10U840VSL	1050	580	577	80	890	80	446	450	840	1090	630	620
11U840VSL	1050	580	622	80	890	80	491	450	840	1090	630	665
12U840VSL	1050	580	666	80	890	80	535	450	840	1090	630	710
4U840VSLT	1060	580	310	80	890	90	179	450	840	1120	630	370
5U840VSLT	1060	580	355	80	890	90	224	450	840	1120	630	415
6U840VSLT	1060	580	399	80	890	90	268	450	840	1120	630	460
7U840VSLT	1060	580	444	80	890	90	313	450	840	1120	630	505
8U840VSLT	1060	580	488	80	890	90	357	450	840	1120	630	550
9U840VSLT	1060	580	533	80	890	90	402	450	840	1120	630	595
10U840VSLT	1060	580	577	80	890	90	446	450	840	1120	630	640

Artikelnummer	Innenabmessungen						Abmessungen Schwingrahmen			Aussenabmessungen in mm		
	L*	B*	H*	Deckeltiefe vorne	Mittelteil Länge	Deckeltiefe hinten	Einschub höhe a	Einschub breite b	Einschub tiefe c	L	B	H
11U840VSLT	1060	580	622	80	890	90	491	450	840	1120	630	685
12U840VSLT	1060	580	666	80	890	90	535	450	840	1120	630	730
4U920VSL	1130	580	310	80	970	80	179	450	920	1170	630	350
5U920VSL	1130	580	355	80	970	80	224	450	920	1170	630	395
6U920VSL	1130	580	399	80	970	80	268	450	920	1170	630	440
7U920VSL	1130	580	444	80	970	80	313	450	920	1170	630	485
8U920VSL	1130	580	488	80	970	80	357	450	920	1170	630	530
9U920VSL	1130	580	533	80	970	80	402	450	920	1170	630	575
10U920VSL	1130	580	577	80	970	80	446	450	920	1170	630	620
11U920VSL	1130	580	622	80	970	80	491	450	920	1170	630	665
12U920VSL	1130	580	666	80	970	80	535	450	920	1170	630	710
4U920VSLT	1140	580	310	80	970	90	179	450	920	1200	630	370
5U920VSLT	1140	580	355	80	970	90	224	450	920	1200	630	415
6U920VSLT	1140	580	399	80	970	90	268	450	920	1200	630	460
7U920VSLT	1140	580	444	80	970	90	313	450	920	1200	630	505
8U920VSLT	1140	580	488	80	970	90	357	450	920	1200	630	550
9U920VSLT	1140	580	533	80	970	90	402	450	920	1200	630	595
10U920VSLT	1140	580	577	80	970	90	446	450	920	1200	630	640
11U920VSLT	1140	580	622	80	970	90	491	450	920	1200	630	685
12U920VSLT	1140	580	666	80	970	90	535	450	920	1200	630	730
4U1000VSL	1210	580	310	80	1050	80	179	450	1000	1250	630	350
5U1000VSL	1210	580	355	80	1050	80	224	450	1000	1250	630	395
6U1000VSL	1210	580	399	80	1050	80	268	450	1000	1250	630	440
7U1000VSL	1210	580	444	80	1050	80	313	450	1000	1250	630	485
8U1000VSL	1210	580	488	80	1050	80	357	450	1000	1250	630	530
9U1000VSL	1210	580	533	80	1050	80	402	450	1000	1250	630	575
10U1000VSL	1210	580	577	80	1050	80	446	450	1000	1250	630	620
11U1000VSL	1210	580	622	80	1050	80	491	450	1000	1250	630	665
12U1000VSL	1210	580	666	80	1050	80	535	450	1000	1250	630	710
4U1000VSLT	1220	580	310	80	1050	90	179	450	1000	1280	630	370
5U1000VSLT	1220	580	355	80	1050	90	224	450	1000	1280	630	415

Artikelnummer	Innenabmessungen						Abmessungen Schwingrahmen			Aussenabmessungen in mm		
	L*	B*	H*	Deckeltiefe vorne	Mittelteil Länge	Deckeltiefe hinten	Einschub höhe a	Einschub breite b	Einschub tiefe c	L	B	H
6U1000VSLT	1220	580	399	80	1050	90	268	450	1000	1280	630	460
7U1000VSLT	1220	580	444	80	1050	90	313	450	1000	1280	630	505
8U1000VSLT	1220	580	488	80	1050	90	357	450	1000	1280	630	550
9U1000VSLT	1220	580	533	80	1050	90	402	450	1000	1280	630	595
10U1000VSLT	1220	580	577	80	1050	90	446	450	1000	1280	630	640
11U1000VSLT	1220	580	622	80	1050	90	491	450	1000	1280	630	685
12U1000VSLT	1220	580	666	80	1050	90	535	450	1000	1280	630	730
4U1080VSL	1290	580	310	80	1130	80	179	450	1080	1330	630	350
5U1080VSL	1290	580	355	80	1130	80	224	450	1080	1330	630	395
6U1080VSL	1290	580	399	80	1130	80	268	450	1080	1330	630	440
7U1080VSL	1290	580	444	80	1130	80	313	450	1080	1330	630	485
8U1080VSL	1290	580	488	80	1130	80	357	450	1080	1330	630	530
9U1080VSL	1290	580	533	80	1130	80	402	450	1080	1330	630	575
10U1080VSL	1290	580	577	80	1130	80	446	450	1080	1330	630	620
11U1080VSL	1290	580	622	80	1130	80	491	450	1080	1330	630	665
12U1080VSL	1290	580	666	80	1130	80	535	450	1080	1330	630	710
4U1080VSLT	1300	580	310	80	1130	90	179	450	1080	1360	630	370
5U1080VSLT	1300	580	355	80	1130	90	224	450	1080	1360	630	415
6U1080VSLT	1300	580	399	80	1130	90	268	450	1080	1360	630	460
7U1080VSLT	1300	580	444	80	1130	90	313	450	1080	1360	630	505
8U1080VSLT	1300	580	488	80	1130	90	357	450	1080	1360	630	550
9U1080VSLT	1300	580	533	80	1130	90	402	450	1080	1360	630	595
10U1080VSLT	1300	580	577	80	1130	90	446	450	1080	1360	630	640
11U1080VSLT	1300	580	622	80	1130	90	491	450	1080	1360	630	685
12U1080VSLT	1300	580	666	80	1130	90	535	450	1080	1360	630	730